

Description

MS21140-0808 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS211400808 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-01-057-3187 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21140-0808 Specifications

| | |
|---|--|
| Fastener Length: | 0.719 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.258 Inches Minimum And 0.260 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.508 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.469 Inches Minimum And 0.532 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21140-0808> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.