

Description

MS21140-0808 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS211400808
Minimum Qty (MOQ):	5
NSN:	5320-01-057-3187
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS21140-0808 Specifications

Fastener Length:	0.719 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.508 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.469 Inches Minimum And 0.532 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21140-0808> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.