

**Description**

Dry film lubrication, flush countersunk style, MS21140S series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21140S0504
Minimum Qty (MOQ):	10
NSN:	5320-01-156-4448
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N MS21140S0504 Specifications

<b>Fastener Length:</b>	0.529 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.162 Inches Minimum And 0.164 Inches Maximum
<b>Head Major Diameter:</b>	0.354 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.219 Inches Minimum And 0.282 Inches Maximum
<b>Minimum Tensile Strength:</b>	1150 Pounds Per Square Inch
<b>Shear Strength:</b>	1980 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	96906-ms21140s0504 Government Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21140S0504> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.