

Description

Dry film lubrication, flush countersunk style, MS21140S series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21140S0504
Minimum Qty (MOQ):	10
NSN:	5320-01-156-4448
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS21140S0504 Specifications

Fastener Length:	0.529 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Head Major Diameter:	0.354 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.219 Inches Minimum And 0.282 Inches Maximum
Minimum Tensile Strength:	1150 Pounds Per Square Inch
Shear Strength:	1980 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	96906-ms21140s0504 Government Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21140S0504> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.