

**Description**

MS21140S0609 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21140S0609
Minimum Qty (MOQ):	2
NSN:	5320-01-193-2440
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS21140S0609 Specifications

<b>Fastener Length:</b>	0.740 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.197 Inches Minimum And 0.199 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.387 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.531 Inches Minimum And 0.595 Inches Maximum
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	98.30 Degrees Minimum And 101.30 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416,ty 2 Cl 2 Fed Spec 2nd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21140S0609> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.