

Description

MS21141-0807 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS211410807
Minimum Qty (MOQ):	10
NSN:	5320-01-057-3181
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141-0807 Specifications

Fastener Length:	0.656 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.130 Inches Minimum And 0.140 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.400 Inches Minimum And 0.432 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.406 Inches Minimum And 0.470 Inches Maximum
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141-0807> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.