

## P/N MS21141S0501

### **Description**

MS21141S0501 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21141S0501

Minimum Qty (MOQ): 10

NSN: 5320-01-470-7175

Schedule B: 8308.20.6000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21141S0501 Specifications

Fastener Length:	0.217 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.062 Inches Minimum And 0.070 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Minimum And 0.272 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.031 Inches Minimum And 0.096 Inches Maximum
Material:	Iron Alloy Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/MS21141S0501">https://military-fasteners.com/rivets/blind+rivets/MS21141S0501</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/MS21141S0501">https://military-fasteners.com/rivets/blind+rivets/MS21141S0501</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/MS21141S0501">https://military-fasteners.com/rivets/blind+rivets/MS21141S0501</a> and selecting the quantity you want then