

Description

MS21141S0501 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141S0501
Minimum Qty (MOQ):	10
NSN:	5320-01-470-7175
Schedule B:	8308.20.6000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141S0501 Specifications

Fastener Length:	0.217 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.062 Inches Minimum And 0.070 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Minimum And 0.272 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.031 Inches Minimum And 0.096 Inches Maximum
Material:	Iron Alloy Overall
Surface Treatment:	Passivate Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141S0501> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.