

**Description**

Fastener Length: 11/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21141S0503
Minimum Qty (MOQ):	10
NSN:	5320-01-199-4446
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS21141S0503 Specifications

<b>Fastener Length:</b>	0.342 Inches Nominal
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.062 Inches Minimum And 0.070 Inches Maximum
<b>Shank Diameter:</b>	0.162 Inches Minimum And 0.164 Inches Maximum
<b>Head Major Diameter:</b>	0.250 Inches Minimum And 0.272 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.156 Inches Minimum And 0.220 Inches Maximum
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416,ty 2 Cl 2 Fed Spec 2nd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141S0503> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.