

Description

Fastener Length: 11/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS21141S0503 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-199-4446 |
| Schedule B: | 7318.16.0060 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141S0503 Specifications

| | |
|---|---|
| Fastener Length: | 0.342 Inches Nominal |
| Head Style: | Straight Pan |
| Head Height: | 0.062 Inches Minimum And 0.070 Inches Maximum |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Head Major Diameter: | 0.250 Inches Minimum And 0.272 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.156 Inches Minimum And 0.220 Inches Maximum |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416,ty 2 Cl 2 Fed Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141S0503> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.