

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21141U0503
Minimum Qty (MOQ):	10
NSN:	5320-01-199-4446
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS21141U0503 Specifications

Fastener Length:	0.342 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.062 Inches Minimum And 0.070 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Head Major Diameter:	0.250 Inches Minimum And 0.272 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.156 Inches Minimum And 0.220 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416,ty 2 Cl 2 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0503> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.