

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21141U0504 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5320-01-311-6332 |
| Schedule B: | 7318.15.2091 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS21141U0504 Specifications

| | |
|---|--|
| Identification Code Color: | Green |
| Fastener Length: | 0.405 Inches Maximum |
| Head Style: | Straight Pan |
| Head Height: | 0.062 Inches Minimum And 0.070 Inches Maximum |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.250 Inches Minimum And 0.272 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.219 Inches Minimum And 0.282 Inches Maximum |
| Minimum Tensile Strength: | 95000 Pounds Per Square Inch |
| Special Features: | The Letter "u" Signifies Single Action Fastener Without Frangible Type Of Locking Collar Or Locking Collar Cap |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0504> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.