

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0506
Minimum Qty (MOQ):	10
NSN:	5320-01-311-6334
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS21141U0506 Specifications

Identification Code Color:	Green
Fastener Length:	0.530 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.062 Inches Minimum And 0.070 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Minimum And 0.272 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.344 Inches Minimum And 0.407 Inches Maximum
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Special Features:	The Letter "u" Signifies Single Action Fastener Without Frangible Type Of Locking Collar Or Locking Collar Cap
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0506> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.