

**Description**

MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS21141U0506                                |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5320-01-311-6334                            |
| Schedule B:             | 7318.15.2091                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



## P/N MS21141U0506 Specifications

|   |  |
|---|--|
| <b>Identification Code Color:</b>                     | Green  |
| <b>Fastener Length:</b>                               | 0.530 Inches Maximum   |
| <b>Head Style:</b>                                    | Straight Pan   |
| <b>Head Height:</b>                                   | 0.062 Inches Minimum And 0.070 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.162 Inches Minimum And 0.164 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.250 Inches Minimum And 0.272 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Lubrication:</b>                                   | Dry Film   |
| <b>Grip Length:</b>                                   | 0.344 Inches Minimum And 0.407 Inches Maximum  |
| <b>Minimum Tensile Strength:</b>                      | 95000 Pounds Per Square Inch   |
| <b>Special Features:</b>                              | The Letter "u" Signifies Single Action Fastener Without Frangible Type Of Locking Collar Or Locking Collar Cap |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall   |
| <b>Surface Treatment:</b>                             | Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve   |
| <b>Surface Treatment:</b>                             | Passivate Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0506> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.