

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0507
Minimum Qty (MOQ):	10
NSN:	5320-01-365-0505
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141U0507 Specifications

Fastener Length:	0.592 Inches Nominal
Head Style:	Tapered Pan
Head Height:	0.062 Inches Minimum And 0.070 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Minimum And 0.272 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.406 Inches Minimum And 0.470 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Locking Collar Green
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 316 Locking Ringiron Alloy 660 Sleeveiron Alloy 660 Stem
Material Document And Classification:	Ams5737 Assn Std 1st Material Response Locking Ring Or Ams5690 Assn Std 2nd Material Response Locking Ringams5737 Assn Std Single Material Response Sleeveams5737 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Locking Ringpassivate Sleeve Or Cadmium Sleeve And Chromate Sleevepassivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ringqq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416 Ty 2,cl 2 Fed Spec 2nd Treatment Response Sleeveqq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0507> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.