

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0602P
Minimum Qty (MOQ):	10
NSN:	5320-01-280-5891
Schedule B:	7318.15.2091
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N MS21141U0602P Specifications

Identification Code Color:	Green
Fastener Length:	0.303 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.305 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.120 Nominal Mills And 0.157 Nominal Centimeters
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve Or Passivate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve Or Qq-p-35 Fed Spec 2nd Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0602P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.