

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0604P
Minimum Qty (MOQ):	25
NSN:	5320-01-353-1416
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141U0604P Specifications

Fastener Length:	0.4280 Inches Nominal
Shank Diameter:	0.1970 Inches Minimum And 0.1990 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.2190 Inches Minimum And 0.2820 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Steel Corrosion Resisting Sleeve steel Corrosion Resisting Stem
Material Document And Classification:	Ams 6737 Assn Std Single Material Response Sleeveams 6737 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve passivate Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeveqq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0604P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.