

**Description**

MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | MS21141U0606                              |
| Minimum Qty (MOQ):      | 10                                        |
| NSN:                    | 5320-01-329-9784                          |
| Schedule B:             | 7318.15.2091                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21141U0606 Specifications

|                                                       |                                                    |
|-------------------------------------------------------|----------------------------------------------------|
| <b>Identification Code Color:</b>                     | Green                                              |
| <b>Fastener Length:</b>                               | 0.533 Inches Nominal                               |
| <b>Head Style:</b>                                    | Tapered Pan                                        |
| <b>Head Height:</b>                                   | 0.125 Inches Minimum And 0.135 Inches Maximum      |
| <b>Shank Diameter:</b>                                | 0.197 Inches Minimum And 0.199 Inches Maximum      |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem             |
| <b>Head Major Diameter:</b>                           | 0.305 Inches Minimum And 0.332 Inches Maximum      |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                               |
| <b>Grip Length:</b>                                   | 0.344 Inches Minimum And 0.407 Inches Maximum      |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch                |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                             |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0606> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.