

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS21141U0606 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-329-9784 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141U0606 Specifications

| | |
|---|--|
| Identification Code Color: | Green |
| Fastener Length: | 0.533 Inches Nominal |
| Head Style: | Tapered Pan |
| Head Height: | 0.125 Inches Minimum And 0.135 Inches Maximum |
| Shank Diameter: | 0.197 Inches Minimum And 0.199 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.305 Inches Minimum And 0.332 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.344 Inches Minimum And 0.407 Inches Maximum |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0606> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.