

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0606P
Minimum Qty (MOQ):	10
NSN:	5320-01-424-5079
Schedule B:	7318.15.8085
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N MS21141U0606P Specifications

Identification Code Color:	Green
Fastener Length:	0.553 Inches Nominal
Head Style:	Tapered Pan
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.305 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.344 Inches Minimum And 0.407 Inches Maximum
Special Features:	Single Action Fastener Installed With A Single Action Tool
Material:	Iron Alloy 660 Mechanical Lock Or Steel Comp 316 Mechanical Lockiron Alloy 660 Sleeveiron Alloy 660 Stem
Material Document And Classification:	Ams 5737 Assn Std 1st Material Response Mechanical Lock Or Ams 5690 Assn Std 2nd Material Response Mechanical Lockams 5737 Assn Std Single Material Response Sleeveams 5737 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Mechanical Lockpassivate Sleeve Or Cadmium Sleeve And Chromate Sleevepassivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Mechanical Lockqq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty 2,cl 2 Fed Spec 2nd Treatment Response Sleeve And Qq-p-416,ty 2,cl 2 Fed Spec 3rd Treatment Response Sleeveqq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0606P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.