

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0610P
Minimum Qty (MOQ):	10
NSN:	5320-01-385-2105
Schedule B:	7318.15.2091
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N MS21141U0610P Specifications

Fastener Length:	0.803 Inches Nominal
Head Style:	Tapered Pan
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.1970 Inches Minimum And 0.1990 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.305 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.594 Inches Minimum And 0.657 Inches Maximum
Material:	Iron Alloy 660 Mechanical Lock Or Steel Comp 316 Mechanical Lock
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Surface Treatment:	Passivate Mechanical Lock
Surface Treatment:	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Passivate Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0610P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.