

**Description**

MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21141U0610P
Minimum Qty (MOQ):	10
NSN:	5320-01-385-2105
Schedule B:	7318.15.2091
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N MS21141U0610P Specifications

<b>Fastener Length:</b>	0.803 Inches Nominal
<b>Head Style:</b>	Tapered Pan
<b>Head Height:</b>	0.125 Inches Minimum And 0.135 Inches Maximum
<b>Shank Diameter:</b>	0.1970 Inches Minimum And 0.1990 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.305 Inches Minimum And 0.332 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.594 Inches Minimum And 0.657 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Mechanical Lock Or Steel Comp 316 Mechanical Lock
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Surface Treatment:</b>	Passivate Mechanical Lock
<b>Surface Treatment:</b>	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Passivate Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0610P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.