

# P/N MS21141U0611

### **Description**

Pan head, green color, alloy material, MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS21141U0611
Minimum Qty (MOQ):	10
NSN:	5320-01-462-8406
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	096320. Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21141U0611 Specifications

Identification Code Color:	Green
Fastener Length:	0.865 Inches Nominal
Head Style:	Tapered Pan
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.305 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.656 Inches Minimum And 0.720 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

# **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/MS21141U0611">https://military-fasteners.com/rivets/blind+rivets/MS21141U0611</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/MS21141U0611">https://military-fasteners.com/rivets/blind+rivets/MS21141U0611</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/MS21141U0611">https://military-fasteners.com/rivets/blind+rivets/MS21141U0611</a> and selecting the quantity you want then