



Military-Fasteners.com

P/N MS21141U0614

Description

MS21141

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21141U0614
Minimum Qty (MOQ):	10
NSN:	5320-01-378-3122
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS21141U0614 Specifications

Identification Code Color:	Green
Fastener Length:	1.199 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.305 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.844 Inches Minimum And 0.907 Inches Maximum
Minimum Tensile Strength:	169000 Pounds Per Square Inch
Shear Strength:	2925 Single Pounds Per Square Inch
Special Features:	Single Action Fastener Without Frangible Type Of Locking Collar Or Locking Collar Cap
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0614> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.