

**Description**

MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0802
Minimum Qty (MOQ):	10
NSN:	5320-01-412-8804
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	096300, Rivets Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21141U0802 Specifications

<b>Head Style:</b>	Undercut Pan No. 2
<b>Head Height:</b>	0.130 Inches Minimum And 0.140 Inches Maximum
<b>Shank Diameter:</b>	0.258 Inches Minimum And 0.260 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.400 Inches Minimum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.094 Inches Minimum And 0.157 Inches Maximum
<b>Shear Strength:</b>	5000 Single Pounds Per Square Inch
<b>Special Features:</b>	Single Action Fastener Without Frangible Type Of Locking Collar Or Locking Collar Cap.
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0802> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.