

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0802
Minimum Qty (MOQ):	10
NSN:	5320-01-412-8804
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	096300, Rivets Brass / Bronze / Copper



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141U0802 Specifications

Head Style:	Undercut Pan No. 2
Head Height:	0.130 Inches Minimum And 0.140 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.400 Inches Minimum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.094 Inches Minimum And 0.157 Inches Maximum
Shear Strength:	5000 Single Pounds Per Square Inch
Special Features:	Single Action Fastener Without Frangible Type Of Locking Collar Or Locking Collar Cap.
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0802> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.