

**Description**

MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0810
Minimum Qty (MOQ):	10
NSN:	5320-01-389-7584
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21141U0810 Specifications

<b>Fastener Length:</b>	0.844 Inches Nominal
<b>Head Style:</b>	Tapered Pan
<b>Head Height:</b>	0.130 Inches Minimum And 0.140 Inches Maximum
<b>Shank Diameter:</b>	0.250 Inches Minimum And 0.260 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.400 Inches Minimum And 0.432 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.594 Inches Minimum And 0.657 Inches Maximum
<b>Special Features:</b>	Single Action Fastener Installed With A Single Action Tool
<b>Material:</b>	Iron Alloy 660 Mechanical Lock Or Steel Comp 316 Mechanical Lockiron Alloy 660 Sleeveiron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std 1st Material Response Mechanical Lock Or Ams 5690 Assn Std 2nd Material Response Mechanical Lockams 5737 Assn Std Single Material Response Sleeveams 5737 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0810> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.