

**Description**

MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0810P
Minimum Qty (MOQ):	10
NSN:	5320-01-424-5082
Schedule B:	7318.15.8085
ECCN:	9A991



NO IMAGE  
AVAILABLE

## P/N MS21141U0810P Specifications

<b>Fastener Length:</b>	0.844 Inches Nominal
<b>Head Style:</b>	Tapered Pan
<b>Head Height:</b>	0.130 Inches Minimum And 0.140 Inches Maximum
<b>Shank Diameter:</b>	0.258 Inches Minimum And 0.260 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.400 Inches Minimum And 0.432 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.594 Inches Minimum And 0.647 Inches Maximum
<b>Special Features:</b>	Single Action Fastener Installed With A Single Action Tool
<b>Material:</b>	Iron Alloy 660 Mechanical Lock Or Steel Comp 316 Mechanical Lockiron Alloy 660 Sleeveiron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std 1st Material Response Mechanical Lock Or Ams 5690 Assn Std 2nd Material Response Mechanical Lockams 5737 Assn Std Single Material Response Sleeveams 5737 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Mechanical Lockpassivate Sleeve Or Cadmium Sleeve And Chromate Sleevepassivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Mechanical Lockqq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty 2,cl 2 Fed Spec 2nd Treatment Response Sleeve And Qq-p-416,ty 2,cl 2 Fed Spec 3rd Treatment Response Sleeveqq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0810P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.