

**Description**

MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0813
Minimum Qty (MOQ):	1
NSN:	5320-01-388-3801
Schedule B:	8302.49.6055
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N MS21141U0813 Specifications

<b>Fastener Length:</b>	1.031 Inches Nominal
<b>Head Style:</b>	Tapered Pan
<b>Head Height:</b>	0.1300 Inches Minimum And 0.1400 Inches Maximum
<b>Shank Diameter:</b>	0.2600 Inches Minimum And 0.2680 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.4000 Inches Minimum And 0.4320 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.7810 Inches Minimum And 0.8450 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Mechanical Lock Or Steel Comp 316 Mechanical Lockiron Alloy 660 Sleeveiron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Mechanical Lock Or Ams 5690 Assn Std Single Material Response Mechanical Lockams 5737 Assn Std Single Material Response Sleeveams 5737 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Mechanical Lockpassivate Sleevepassivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Mechanical Lockqq-p-35 Fed Spec Single Treatment Response Sleeveqq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0813> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.