

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U0816
Minimum Qty (MOQ):	2
NSN:	5320-01-383-6102
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141U0816 Specifications

Fastener Length:	1.2190 Inches Nominal
Head Style:	Tapered Pan
Head Height:	0.1300 Inches Minimum And 0.1400 Inches Maximum
Shank Diameter:	0.2600 Inches Minimum And 0.2680 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.4000 Inches Minimum And 0.4320 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.9690 Inches Minimum And 1.0320 Inches Maximum
Material:	Iron Alloy 660 Locking Ring Or Steel Comp 316 Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Locking Ring Or Ams 5690 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Sleeve
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U0816> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.