

**Description**

MS21141 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U1004
Minimum Qty (MOQ):	10
NSN:	5320-01-456-6412
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS21141U1004 Specifications

<b>Fastener Length:</b>	0.506 Inches Nominal
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.131 Inches Minimum And 0.141 Inches Maximum
<b>Shank Diameter:</b>	0.310 Inches Minimum And 0.312 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.480 Inches Minimum And 0.522 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.219 Inches Minimum And 0.282 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U1004> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.