

Description

MS21141 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21141U1007
Minimum Qty (MOQ):	10
NSN:	5320-01-338-4192
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21141U1007 Specifications

Fastener Length:	0.693 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.131 Inches Minimum And 0.141 Inches Maximum
Shank Diameter:	0.310 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.480 Inches Minimum And 0.522 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.406 Inches Minimum And 0.470 Inches Maximum
Special Features:	Single Action Fastener W/o Frangible Type Of Locking Collar Or Locking Collar Cap
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416,ty 2,cl 2 Fed Spec 2nd Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U1007> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.