

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21141U1012
Minimum Qty (MOQ):	1
NSN:	5320-01-505-9894
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS21141U1012 Specifications

Identification Code Color:	Green
Fastener Length:	1.006 Inches Nominal
Head Style:	Tapered Pan
Head Height:	0.224 Inches Minimum And 0.319 Inches Maximum
Shank Diameter:	0.310 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.373 Inches Minimum
Lubrication:	Cetyl Alcohol
End Item Identification:	Rib,inboard Hinge, Aircraft
Grip Length:	1.218 Inches Minimum
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Inavy)rivet,blind
Special Features:	The Letter "u" Signifies Single Action Fastener Without Frangible Type Of Locking Collar Or Locking Collar Cap
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Sleeve Or Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve Or Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS21141U1012> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.