

Description

bearing double row rod end -external thread self aligning

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS211518C
Minimum Qty (MOQ):	1
NSN:	3110-01-006-4014
ECCN:	EAR99
National Motor Freight:	114820, Bearings / Bushings Noi Ball / Roller

NO IMAGE
AVAILABLE

P/N MS21151-8C Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Shank Diameter:	0.4280 Inches Minimum And 0.4480 Inches Maximum
Shank Style:	Externally Threaded
Overall Length:	2.3440 Inches Nominal
Bore Diameter:	0.2497 Inches Minimum And 0.2500 Inches Maximum
Overall Outside Diameter:	0.9280 Inches Minimum And 0.9480 Inches Maximum
Lubrication Material:	Grease
Shank Thread Length:	1.0940 Inches Minimum And 1.1560 Inches Maximum
Outer Ring Width:	0.4280 Inches Minimum And 0.4480 Inches Maximum
Inner Ring Width:	0.5880 Inches Minimum And 0.5930 Inches Maximum
Length From Bore Center To Shank End:	1.8650 Inches Minimum And 1.8850 Inches Maximum
Seal Quantity:	2
Bearing Seal Type:	Contact
Alignment Type:	Self-aligning
Self-alignment Location:	Internal
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Self-alignment Angle:	10.00 Degrees Nominal
Special Features:	Nas513 Keyway, filled With 80 Pct Of Specified Lubricant
Lubrication Material Document And Classification:	Mil-g-81322 Mil Spec Single Material Response
Material:	Plastic Polytetrafluoroethylene Seal
Material:	Steel Comp 4130 Outer Ring
Material:	Steel Comp 4130 Rod End Body
Material:	Steel Comp E52100 Ball
Material:	Steel Comp E52100 Inner Ring
Material Document And Classification:	Ams 3652 Assn Std Single Material Response Seal
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Outer Ring
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Rod End Body
Material Document And Classification:	Mil-s-7420 Mil Spec Single Material Response Ball
Material Document And Classification:	Mil-s-7420 Mil Spec Single Material Response Inner Ring

Surface Treatment:	Cadmium All External/exposed Metal Surfaces
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response All External/exposed Metal Surfaces
Style Designator:	Double Row, Staggered, Ball
Thread Series Designator:	Unjf

How to Order

Order this rod end bearing from our inventory online by visiting <https://military-fasteners.com/bearings/rod+end+bearings/MS21151-8C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.