

P/N MS21206-C12

Description

Hole Diameter: 3/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS21206C12

SKU / Model: MS21206C12

Minimum Qty (MOQ): 50

NSN: 5310-01-057-3114

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,



^{*} See page 2 for technical characteristics

P/N MS21206-C12 Specifications

Hole Diameter:	0.752 Inches Minimum And 0.756 Inches Maximum
Outside Diameter:	1.340 Inches Minimum And 1.350 Inches Maximum
Recess Diameter:	0.903 Inches Minimum And 0.913 Inches Maximum
Material Thickness:	0.071 Inches Minimum And 0.085 Inches Maximum
Hardness Rating:	38.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	89.0 Degrees Minimum And 91.0 Degrees Maximum
Material:	Steel Comp 4130 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed

How to Order

Order this recessed washer from our inventory online by visiting https://military-fasteners.com/washers/recessed+washers/MS21206-C12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.