

Description

Hole Diameter: 3/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS21206C12](#)

SKU / Model:	MS21206C12
Minimum Qty (MOQ):	50
NSN:	5310-01-057-3114
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS21206-C12 Specifications

Hole Diameter:	0.752 Inches Minimum And 0.756 Inches Maximum
Outside Diameter:	1.340 Inches Minimum And 1.350 Inches Maximum
Recess Diameter:	0.903 Inches Minimum And 0.913 Inches Maximum
Material Thickness:	0.071 Inches Minimum And 0.085 Inches Maximum
Hardness Rating:	38.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	89.0 Degrees Minimum And 91.0 Degrees Maximum
Material:	Steel Comp 4130 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS21206-C12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.