

Description

Hole Diameter: 5/8",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS21206C9](#)

| | |
|-------------------------|---|
| SKU / Model: | MS21206C9 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-01-058-6838 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



P/N MS21206-C9 Specifications

| | |
|---|--|
| Hole Diameter: | 0.564 Inches Minimum And 0.568 Inches Maximum |
| Outside Diameter: | 0.999 Inches Minimum And 1.009 Inches Maximum |
| Recess Diameter: | 0.684 Inches Minimum And 0.694 Inches Maximum |
| Material Thickness: | 0.071 Inches Minimum And 0.085 Inches Maximum |
| Hardness Rating: | 38.0 Rockwell C Minimum And 45.0 Rockwell C Maximum |
| Recess Angle: | 90.0 Degrees Nominal |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-658 Mil Spec 1st Material Response Overall Or Mil-s-18729 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS21206-C9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.