

**Description**

Hole Diameter: 5/8",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS21206C9](#)

SKU / Model:	MS21206C9
Minimum Qty (MOQ):	100
NSN:	5310-01-058-6838
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE  
AVAILABLE

## P/N MS21206-C9 Specifications

<b>Hole Diameter:</b>	0.564 Inches Minimum And 0.568 Inches Maximum
<b>Outside Diameter:</b>	0.999 Inches Minimum And 1.009 Inches Maximum
<b>Recess Diameter:</b>	0.684 Inches Minimum And 0.694 Inches Maximum
<b>Material Thickness:</b>	0.071 Inches Minimum And 0.085 Inches Maximum
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Material:</b>	Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-658 Mil Spec 1st Material Response Overall Or Mil-s-18729 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS21206-C9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.