

Description

MS21206 series washer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS21206C16 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-01-150-4010 |
| Schedule B: | 7318.22.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N MS21206C16 Specifications

| | |
|---|---|
| Hole Diameter: | 1.002 Inches Minimum And 1.006 Inches Maximum |
| Outside Diameter: | 1.788 Inches Minimum And 1.798 Inches Maximum |
| Recess Diameter: | 1.219 Inches Minimum And 1.229 Inches Maximum |
| Material Thickness: | 0.124 Inches Minimum And 0.139 Inches Maximum |
| Hardness Rating: | 38.0 Rockwell C Minimum And 45.0 Rockwell C Maximum |
| Recess Angle: | 89.0 Degrees Minimum And 91.0 Degrees Maximum |
| Special Features: | Chamfer 0.030 In. Min 0.040 In. Max By 45 Deg Outside Left Corner |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS21206C16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.