

P/N MS21207-10-6

Description

Screw part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS21207106

Minimum Qty (MOQ): 20 EA

NSN: 5305-01-451-5580

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N MS21207-10-6 Specifications

| Fastener Length: | 0.375 Inches Nominal |
|--|---|
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.359 Inches Minimum And 0.385 Inches Maximum |
| Head Height: | 0.063 Inches Minimum And 0.072 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| lii End Item Identification: | Spec Item |
| Nonmachine Thread Style: | Dog Type (type B Or C) |
| Countersink Angle: | 100.0 Degrees Nominal |
| Nonmachine Nominal Thread Diameter: | 0.190 Inches |
| Material: | Steel Overall |
| Material Document And Classification: | Mil-s-6033 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty2,cl2aasklc50 Fed Spec Single Treatment Response Overall |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS21207-10-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS21207-10-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS21207-10-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms21207-10-6 and selecting the quantity you want https://military-fasteners.com/screws/ms21207-10-6 and selecting the quantity you want https://military-fasteners.com/screws/ms21207-10-6 and selecting the quantity you want https://military-fasteners.com/screws/ms21207-10-6 and selecting the property of the