

Description

length: 0.562", thread: 3/8-24, helicoil insert corrosion resistant steel, fine thread, dry film lube, MS21209 series insert

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS21209F615L |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5325-00-680-8768 |
| Schedule B: | 7318.16.0060 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS21209F6-15L Specifications

| | |
|---------------------------------------|--|
| Thread Direction: | Right-hand |
| Length: | 0.562 Inches Nominal |
| Insert Size: | 0.448 In.min,0.468 In.max |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall |
| Material Document And Classification: | Aisi/sae Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Style Designator: | Coil |
| Specification/standard Data: | 81205-bacs13 Manufacturers Specification |

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/MS21209F6-15L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.