

Description

Assembled washer, 1/4-28 unjf thread, A grade steel, MS21244 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MSY03919](#)

SKU / Model:	MS212444
Minimum Qty (MOQ):	10
NSN:	5310-00-126-5753
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21244-4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Washer Outside Diameter:	0.530 Inches Minimum And 0.560 Inches Maximum
Counterbore Diameter:	0.299 Inches Minimum Nut And 0.309 Inches Maximum Nut
Overall Height:	0.365 Inches Minimum And 0.405 Inches Maximum
Nut Style:	Flat With Turned Back Edge
Nut Counterbore Depth:	0.172 Inches Minimum Nut And 0.192 Inches Maximum Nut
Width Across Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Comp 302 Washer Or Steel Comp 321 Washer
Material:	Steel Nut
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Passivate Washer
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Washer
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Nut
Nondefinitive Spec/std Data:	A Grade

How to Order

Order this plain castellated hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+castellated+hexagon+nuts/MS21244-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.