



★ FASTENERS

Military-Fasteners.com

P/N MS21250-03008

Description

length: 0.94", grip: 0.50", thread: 10-32, external wrenching, flanged, 12 point, cadmium plated steel alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125003008
Minimum Qty (MOQ):	5
NSN:	5306-01-028-0179
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21250-03008 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.420 Inches Minimum And 0.460 Inches Maximum
Fastener Length:	0.930 Inches Minimum And 0.950 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.255 Inches Minimum And 0.275 Inches Maximum
Width Between Flats:	0.240 Inches Minimum And 0.260 Inches Maximum
Extended Washer Diameter:	0.340 Inches Minimum And 0.350 Inches Maximum
Extended Washer Thickness:	0.045 Inches Minimum And 0.065 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-03008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.