

Description

Fastener Length: 3-17/64", Thread: 1/4-28, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2125004044 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-048-1128 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21250-04044 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.492 Inches Minimum And 0.532 Inches Maximum |
| Fastener Length: | 3.252 Inches Minimum And 3.272 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.300 Inches Nominal |
| Width Between Flats: | 0.312 Inches Nominal |
| Extended Washer Diameter: | 0.428 Inches Minimum And 0.438 Inches Maximum |
| Extended Washer Thickness: | 0.069 Inches Nominal |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 2.740 Inches Minimum And 2.760 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-04044> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.