

**Description**

Fastener Length: 1-1/32", Thread: 1/4-24, Thread Length: 19/32", MS21250 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS2125005007                              |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-01-327-0365                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N MS21250-05007 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.599 Inches Nominal  |
| <b>Fastener Length:</b>                               | 1.036 Inches Nominal  |
| <b>Head Style:</b>                                    | Double Hexagon Extended Washer  |
| <b>Head Height:</b>                                   | 0.348 Inches Nominal  |
| <b>Width Between Flats:</b>                           | 0.375 Inches Nominal  |
| <b>Extended Washer Diameter:</b>                      | 0.521 Inches Minimum And 0.531 Inches Maximum   |
| <b>Extended Washer Thickness:</b>                     | 0.082 Inches Nominal  |
| <b>Grip Diameter:</b>                                 | 0.3110 Inches Minimum And 0.3120 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches  |
| <b>Grip Length:</b>                                   | 0.427 Inches Minimum And 0.447 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall                                       |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-05007> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.