

Description

Fastener Length: 1-3/32", Thread: 1/4-24, Thread Length: 37/64", 12 point, external wrenching

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125005008
Minimum Qty (MOQ):	5
NSN:	5306-00-990-6918
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21250-05008 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.579 Inches Nominal
Fastener Length:	1.099 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.348 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.438 Inches Maximum
Extended Washer Thickness:	0.082 Inches Nominal
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-05008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.