



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N MS21250-05014**

## Description

length: 1.474", grip: 0.875", thread: 5/16-24, external wrenching bolt, flanged, 12 point, cadmium plated steel alloy, undrilled head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS2125005014
Minimum Qty (MOQ):	10
NSN:	5306-00-057-8703
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21250-05014 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.579 Inches Minimum
<b>Fastener Length:</b>	1.474 Inches Nominal
<b>Head Style:</b>	Double Hexagon Extended Washer
<b>Head Height:</b>	0.348 Inches Nominal
<b>Width Between Flats:</b>	0.360 Inches Minimum And 0.375 Inches Maximum
<b>Extended Washer Diameter:</b>	0.521 Inches Minimum And 0.531 Inches Maximum
<b>Extended Washer Thickness:</b>	0.082 Inches Nominal
<b>Grip Diameter:</b>	0.3110 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-05014> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.