

P/N MS21250-05040

Military-Fasteners.com

Description

length: 3.099", grip: 2.500", thread: 5/16-24, external wrenching bolt, flanged, 12 point, cadmium plated steel alloy, undrilled head

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS2125005040
Minimum Qty (MOQ):	2
NSN:	5306-01-152-4934
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21250-05040 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.579 Inches Minimum
Fastener Length:	3.099 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.348 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Extended Washer Thickness:	0.082 Inches Nominal
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	2.399 Inches Minimum And 2.601 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Type li Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/MS21250-05040</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.