



Military-Fasteners.com

P/N MS21250-05068

Description

Fastener Length: 4-55/64", Thread: 1/4-24, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2125005068
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-333-6391
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21250-05068 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.496 Inches Minimum And 0.619 Inches Maximum
Fastener Length:	4.839 Inches Minimum And 4.859 Inches Maximum
Head Style:	Double Hexagon Extended Washer
Head Height:	0.348 Inches Nominal
Width Between Flats:	0.375 Inches Nominal
Extended Washer Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Extended Washer Thickness:	0.082 Inches Nominal
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	4.240 Inches Minimum And 4.260 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21250-05068> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.