

P/N MS21250-06015

Military-Fasteners.com

Description

Fastener Length: 1-37/64", Thread: 3/8-24, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS2125006015
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-326-3398
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21250-06015 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.645 Inches Nominal
Fastener Length:	1.582 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.438 Inches Nominal
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.091 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.927 Inches Minimum And 0.947 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/MS21250-06015</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.